

# TROPICAL

---

\*\*\*\*\* MATERIAL SAFETY DATA SHEET \*\*\*\*\*

IPE + MARINE OIL, CMS SERIES Page: 1

PRODUCT CODE: BLIMO250

---

\*\*\*\*\* SECTION I MANUFACTURER IDENTIFICATION \*\*\*\*\*

---

COMPANY NAME : TROPICAL FOREST PRODUCTS.  
COMPANY ADDRESS: 6200 TOMKIN ROAD  
COMPANY ADDRESS: MISSISSAUGA, ON, CA, L5T 1X7  
INFORMATION PHONE: (905) 672-8000  
DATE PRINTED: 10/1/21  
MSDS PREPARED BY: BRIAN LOTZ.

---

\*\*\*\*\* SECTION II HAZARDOUS INGREDIENTS \*\*\*\*\*

---

VAPOR PRESSURE WEIGHT  
REPORTABLE COMPONENTS CAS NUMBER MM HG @ TEMP PERCENT

---

MINERAL SPIRITS 64742-47-8 3.4 68F 20 TO 25%  
Octamethylcyclotetrasiloxane 556-67-2 .9 77F 5 TO 10%

---

\*\*\*\*\* SECTION III HAZARDS IDENTIFICATION \*\*\*\*\*

---

HMIS CODES: HEALTH: 2  
FLAMMABILITY: 2  
REACTIVITY: 0  
PERS. PROTECTION: H  
PRIMARY ROUTES OF EXPOSURE: INHALATION, SKIN OR EYE CONTACT,  
INGESTION.  
EFFECTS OF ACUTE OVEREXPOSURE:  
INHALATION: OVEREXPOSURE TO VAPORS MAY CAUSE HEADACHE, DIZZINESS AND  
NAUSEA.  
SKIN: THIS MATERIAL MAY CAUSE IRRITATION. FREQUENT OR PROLONGED  
CONTACT MAY RESULT IN ABSORPTION OF HARMFUL AMOUNTS.  
EYES: THIS MATERIAL MAY BE AN EYE IRRITANT.  
INGESTION: NOT APPLICABLE.  
MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: NONE WHEN USED IN  
ACCORDANCE WITH SAFE HANDLING INSTRUCTIONS.

---

\*\*\*\*\* SECTION IV FIRST AID PROCEDURES \*\*\*\*\*

---

EYES: FLUSH WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES AND SEEK  
MEDICAL ATTENTION

\*\*\*\*\* MATERIAL SAFETY DATA SHEET \*\*\*\*\*

BLACK LABEL IPE + MARINE OIL, CMS SERIES Page: 1

PRODUCT CODE: BLIMO250

---

# TROPICAL

---

-----  
SKIN: PROMPTLY WASH WITH SOAP AND WATER. REMOVE AND WASH ANY CONTAMINATED CLOTHING.

INHALATION: REMOVE VICTIM TO FRESH AIR IMMEDIATELY. GIVE OXYGEN IF BREATHING IS DIFFICULT. GIVE ARTIFICIAL RESPIRATION IF VICTIM IS NOT BREATHING. IF RESPIRATORY SYMPTOMS DEVELOP, SEEK MEDICAL ATTENTION AT ONCE

INGESTION: IF INGESTED DO NOT INDUCE VOMITING. KEEP PERSON WARM, QUIET, AND SEEK MEDICAL ATTENTION.

-----  
\*\*\*\*\* SECTION V FIRE FIGHTING MEASURES \*\*\*\*\*

FLASH POINT: 104F METHOD USED: TCC

FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER: .7 UPPER: 6

EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL WATER FOG  
SPECIAL FIREFIGHTING PROCEDURES: WATER FOG SHOULD BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD UP AND POSSIBLE AUTOIGNITION OR EXPLOSION.

UNUSUAL FIRE AND EXPLOSION HAZARDS: HANDLE AS FLAMMABLE LIQUID. VAPORS MAY BE EXPLOSIVE.

-----  
\*\*\*\*\* SECTION VI ACCIDENTAL RELEASE MEASURES \*\*\*\*\*

SPILL PROCEDURE: REMOVE ALL SOURCES OF IGNITION. VENTILATE AREA. ABSORB SPILL WITH ABSORBENT MATERIAL SUCH AS SAWDUST, VERMICULITE OR SAND AND PLACE MATERIAL INTO A CLOSED CONTAINER. IF LARGE SPILL, DIKE AREA TO PREVENT THIS MATERIAL FROM ENTERING WATER SYSTEMS OR SEWERS. WEAR PROTECTIVE EQUIPMENT DURING CLEANUP. FOLLOW ALL LOCAL, STATE AND FEDERAL HAZARDOUS WASTE REGULATIONS REGARDING DISPOSAL OF WASTES.

-----  
\*\*\*\*\* SECTION VII HANDLING AND STORAGE \*\*\*\*\*

HANDLING: KEEP CONTAINERS CLOSED WHEN NOT IN USE, AND PROPERLY LABELED  
WARNING: RAGS, STEEL WOOL OR WASTE SOAKED WITH THIS PRODUCT MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED, WATER FILLED CONTAINER

STORAGE: AVOID EXCESSIVE HEAT THAT COULD BUILD PRESSURE IN CLOSED CONTAINERS.

-----  
\*\*\*\*\* SECTION VIII EXPOSURE CONTROLS / PERSONAL PROTECTION \*\*\*\*\*

PROTECTIVE EYEWEAR: WEAR FACE SHIELD OR CHEMICAL GOGGLES TO PROTECT

# TROPICAL

---

\*\*\*\*\* MATERIAL SAFETY DATA SHEET \*\*\*\*\*

BLACK LABEL IPE + MARINE OIL, CMS SERIES Page: 1

PRODUCT CODE: BLIMO250

-----

AGAINST SPLASHING OF LIQUID.

PROTECTIVE GLOVES: CHEMICAL RESISTANT NITRILE, NEOPRENE OR RUBBER

GLOVES REQUIRED FOR PROLONGED OR REPEATED CONTACT.

PROTECTIVE CLOTHING: WEAR PROTECTIVE CLOTHING TO PREVENT SKIN CONTACT

RESPIRATORY EQUIPMENT: NIOSH / OSHA APPROVED RESPIRATOR SUITABLE FOR

MATERIALS LISTED IN SECTION II RECOMMENDED TO PREVENT THE INHALATION

OF VAPORS OR SPRAY MISTS WHEN THE TLV OR PEL IS EXCEEDED.

CONTAMINATED EQUIPMENT: WASH CONTAMINATED CLOTHING / EQUIPMENT BEFORE

REUSE OR DISPOSE OF PROPERLY

GENERAL PRECAUTIONS: NEVER EAT, DRINK, OR SMOKE IN WORK AREA. WASH

THOROUGHLY AFTER USING THIS PRODUCT ESPECIALLY BEFORE EATING,

DRINKING, OR SMOKING

-----

\*\*\*\*\* SECTION IX PHYSICAL/CHEMICAL CHARACTERISTICS \*\*\*\*\*

-----

PHYSICAL APPEARANCE: LIGHT VISCOSITY LIQUID WITH CHARACTERISTIC

SOLVENT ODOR

VOLATILE WEIGHT PERCENT (INCLUDES EXEMPT): 36%

BOILING RANGE: 342F – 413F SPECIFIC GRAVITY (H2O = 1): 0.91

COATING V.O.C. 2.09 lb/gl MATERIAL V.O.C. 1.84 lb/gl

250 g/l 221 g/l

-----

\*\*\*\*\* SECTION X STABILITY / REACTIVITY \*\*\*\*\*

-----

STABLE: YES.

REACTIVITY: NOT REACTIVE.

HAZARDOUS POLYMERIZATION: NOT APPLICABLE.

HAZARDOUS DECOMPOSITION PRODUCTS: INCOMPLETE COMBUSTION CAN YIELD

CARBON DIOXIDE, CARBON MONOXIDE AND TOXIC VAPORS

DISCLAIMER: THE INFORMATION IN THIS DATA SHEET IS BELIEVED TO BE

ACCURATE AND TRUE AT THE TIME OF PREPARATION. THIS IS NOT A WARRANTY

OF PRODUCT OR PRODUCT SPECIFICATION. THE END USER OF THIS PRODUCT IS

ADVISED TO VERIFY IN ADVANCE THAT THE INFORMATION IN THIS SHEET IS

CURRENT, APPLICABLE AND SUITABLE TO THEIR CIRCUMSTANCES.

---

1-855-344-4500

6200 Tomken Rd Mississauga, ON - L5T 1X7 - Canada

@tropicalforestproducts

tropicalforestproducts.com

info@tropicalforestproducts.com