

DATE PREPARED: 10/30/24

TROPICAL

SAFETY DATA SHEET

TROPICAL-PRO™ WOOD END SEALER - Glycol Formula

1. IDENTIFICATION

Identity (as used on label and listings): Tropical-Pro Wood End Sealer - Glycol
Formula Chemical Family/Specific Type: Water-based emulsions / aqueous emulsion of wax
Recommended Use: Sealer coating for the ends of logs and lumber

| | | | |
|----------------------|--------------------------|---------------------------------|--------------|
| <u>Manufacturer:</u> | U-C Coatings, LLC | <u>Telephone Number:</u> | 716-833-9366 |
| | P. O. Box 1066 | <u>Fax Number:</u> | 716-833-0120 |
| | Buffalo, NY 14215 U.S.A. | <u>Emergency Telephone No.:</u> | 716-833-9366 |

2. HAZARD(S) IDENTIFICATION

Health Hazards: Ingestion Category 4
 Skin irritation Category 3
 Eye irritation Category 2B

Hazard Pictogram:



Signal Word: **WARNING**

Hazard Statements: Physical Hazards: None

Health Hazards: H316 Causes mild skin irritation
 H320 Causes eye irritation

Environmental Hazards: This substance is not expected to be toxic to aquatic organisms. However, it is still advised that this substance does not enter the environment.

Precautionary Statements:

| | | |
|--------------------|------|---|
| <u>Prevention:</u> | P264 | Wash affected areas thoroughly after handling |
| | P280 | Wear protective gloves and eye protection |
| <u>Response:</u> | P331 | IF SWALLOWED: Rinse mouth. Drink large amounts of water. Do not induce vomiting (aspiration hazard). Seek medical help immediately for ingestion of wax and soap. |
| | P302 | IF ON SKIN: Wash with plenty of with soap and water. Remove contaminated clothing. If irritation persists, seek medical attention. |
| | P305 | IF IN EYES: Flush eyes immediately with large amounts of water, using soap if possible. Remove contact lenses if present and easy to do. If irritation continues, seek medical attention. |
| <u>Storage:</u> | | Store above 5°C / 40°F. Product can be damaged by freezing. |
| <u>Disposal:</u> | P501 | Dispose of contents/container in accordance with local, regional and federal regulations. |

NFPA/HMIS Ratings (scale 0-4): HEALTH = 1 FIRE = 1 REACTIVITY = 0 (0 = Minimal Hazard 4 = Severe Hazard)
 Protective Equipment: Protective gloves and eye protection

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Characterization: Mixture / water-based emulsion

| | | | | |
|--------------------------------|---------------|----------------|------------|--------|
| <u>Main Ingredient:</u> | Petroleum Wax | <u>CAS No.</u> | 64742-61-6 | 25-30% |
| <u>Classified Ingredients:</u> | None | | | |

No other classified ingredients are present which contribute to this product's GHS Hazard Categorization as prescribed by OSHA's Hazard Communication 29 CFR 1910.1200

PRODUCT NAME: TROPICAL-PRO WOOD END SEALER - Glycol Formula**4. FIRST AID MEASURES**

- After Eye Contact: Flush eyes immediately with large amounts of water, using soap if possible. Remove contact lenses if present and easy to do. If irritation continues, seek medical attention.
- After Skin Contact: Wash with plenty of soap and water. Remove contaminated clothing. If irritation persists, seek medical attention.
- After Swallowing: Rinse mouth. Drink large amounts of water. Do not induce vomiting (aspiration hazard). Seek medical help immediately for ingestion of wax and soap.
- Most important symptoms and effects, both acute and delayed: No further relevant information available.
- Indication of any immediate medical attention and special treatment needed: No further relevant information available.

5. FIRE FIGHTING MEASURES

- Extinguishing Media: Water spray, dry chemical, carbon dioxide (CO₂), foam. Do not direct solid stream of water or foam into burning pools.
- Other Fire or Combustion Hazards: Incomplete combustion can produce carbon monoxide.
- Fire Fighting Instructions: Avoid breathing smoke and vapor.
- Fire Fighting Equipment: Self-contained breathing apparatus and protective clothing.

6. ACCIDENTAL RELEASE MEASURES

- Personal Protection: Wear protective gloves and eye protection plus rubber boots when containing large spills.
- Precautions: Do not allow to enter sewers / surface or ground water.
- Containment and Clean-up: Large spills: contain with dikes, collect, and filter for reuse.
Small spills: collect or absorb with oil absorbent pads.
Clean contaminated areas with soap and water. All spill response and disposal should be carried out in accordance with local, regional and federal regulations.

7. HANDLING AND STORAGE

- General: Keep containers closed to minimize evaporation and skin formation.
- Handling: Use normal precautions and protective equipment to avoid exposure to eyes and skin.
- Storage: Store at ambient temperature, above 5°C / 40°F. Product can be damaged by freezing.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

- Ventilation: Good ventilation in work area, atmospheric pressure.
- Personal Protection: Eyes: safety glasses or splash goggles
Hands: protective gloves
Other: synthetic apron for cleanliness

9. PHYSICAL & CHEMICAL CHARACTERISTICS

- Physical State: Liquid Odor: slight petroleum oil odor
- Appearance/Color: White or colored liquid of paint-like consistency
- Viscosity: 3,500 - 4,500 Cps at 25°C / 77°F (LVT Brookfield)
- Flash Point: No flash - boils at 100°C / 212°F Auto ignition temperature: n/a
- Boiling Point: 100°C / 212°F Melting Point: 0°C / 32°F

PRODUCT NAME: TROPICAL-PRO WOOD END SEALER - Glycol Formula**9. PHYSICAL & CHEMICAL CHARACTERISTICS (continued)**

Vapor Pressure: same as water
Vapor Density (air = 1): same as water
Solubility In Water: infinitely diluteable
Specific Gravity: 0.97 - 0.99 typical
Evaporation Rate (butyl acetate = 1): <1
Volatile Organic Compounds: None
Volatile Hazardous Air Pollutants: None
Organic Hazardous Air Pollutant Solvents: None.

10. STABILITY AND REACTIVITY

Reactivity: Non-reactive under normal temperatures and conditions.
Chemical Stability: Stable under normal temperatures and conditions.
Possibility of Hazardous Reactions: Under normal temperatures and conditions, hazardous reactions will not occur.
Conditions to Avoid: None known.
Incompatible Materials: Strong oxidizing agents.
Hazardous Decomposition Products: Under normal temperatures and conditions, hazardous decomposition products should not be produced. Burning may produce carbon monoxide and/or carbon dioxide.

11. TOXICOLOGICAL INFORMATION

No known health hazard, no data available.

12. ECOLOGICAL INFORMATION

No data available.

13. DISPOSAL CONSIDERATIONS

Not a hazardous waste. Where recovery and reuse is not possible, dry water out of product and dispose of as an wax industrial waste or by incineration where permitted under local, regional, or federal regulations.

14. TRANSPORTATION INFORMATION

ADR/RID: Not regulated
 IMDG: Not regulated
 ICAO/IATA: Not regulated

15. REGULATORY INFORMATION

The ingredients in this product are in the TSCA, MITI, AICS, DSL inventories.

16. OTHER INFORMATION

This SDS was prepared 30 October, 2024.